


CUTTING STRAIGHT EDGES


CAUTION DO NOT FORCE THE TOOL. It will do the job better and safer at the rate for which it was designed.




(A)
Loosen the Adjustable
Cutting Guide retaining
thumbscrew




(B)
Position the Adjustable
Cutting Guide to desired
cut length



(C)
Tighten the retaining
thumbscrew




(D)
Place the tile against the
Ruler/Stop and Cutting
Guide




(E)
Turn the motor ON



(F)
Verify cooling flow on both
sides of the blade



(G)
Perform the cut



(H)
Turn the motor OFF when
work is complete


CUTTING 45° MITERS

The MK-370EXP Saw is designed with an adjustable Cutting Head for precision 45° Miter Cuts.


CAUTION DO NOT FORCE THE TOOL. It will do the job better and safer at the rate for which it was designed.




(A)
Loosen the Cutting Head
Pivot, Retaining Knob




(B)
Pivot the Cutting Head to
the 45° cutting position




(C)
Tighten the Cutting Head,
Pivot Retaining Knob




(D)
Loosen the Adjustable
Cutting Guide retaining
thumbscrew




(E)
Position the Adjustable
Cutting Guide to desired
cut length




(F)
Tighten the retaining
thumbscrew



(G)
Place the tile against the
Ruler/Stop and Cutting
Guide




(H)
Turn the motor ON




(I)
Verify cooling flow on both
sides of the blade


CUTTING 45° MITERS (CONT...)



(J)
Perform the cut



(K)
Turn the motor OFF
when work is complete




(L)
Return the Cutting Head
to the upright position
when complete


CUTTING

To cut diagonal, the Dual 45° Flat Angle Guide (MK Diamond Part No. 134557-MK) should be used.


CAUTION DO NOT FORCE THE TOOL. It will do the job better and safer at the rate for which it was designed.



(A)
Place the Adjustable
Cutting Guide



(B)
Place the Dual 45° Flat
Angle Guide on the Ruler/
Stop




(C)
Position the Dual 45° Flat
Angle Guide and tighten
the retaining knob


When cutting the tile in two equal halves, align the tile in the V-notch of the Movable Cutting Table support.




(D)
Align the tile against the
45° Flat Angle Guide
and the Ruler/Stop




(E)
Turn the motor ON



(F)
Verify cooling flow on both
sides of the blade



(G)
Perform the cut



(H)
Turn the motor OFF when
work is complete